



autOTEK
EVOLUTION OF POWER

THE DNA OF
AMERICAN
CAR AUDIO

STREET MACHINE AMPLIFIERS



autohifi TESTSIEGER
Autotek A1800
Oberklasse **58**
Preis/Leistung ★★★★★
Ausgabe 6/2011

A1800 MONOBLOCK

- 1 x 425 Watts RMS into 4 Ohms
 - 1 x 800 Watts RMS into 2 Ohms
 - 1 x 850 Watts Max. into 4 Ohms
 - 1 x 1600 Watts Max. into 2 Ohms
 - RCA In- and Outputs
 - Lowpassfilter 40 - 150 Hz
 - Highpass/Subsonicfilter 15 - 55 Hz
 - Operation-Mode: LP-BP / Full / HP
 - Bass Boost 0 - 12 dB
 - Bass Remote Controller
 - Illuminated Logo-Badge
 - Dimensions: 237 x 55 x 480 mm
- 1 x 425 Watt RMS an 4 Ohm
 - 1 x 800 Watt RMS an 2 Ohm
 - 1 x 850 Watt Max. an 4 Ohm
 - 1 x 1600 Watt Max. an 4 Ohm
 - Cinch Ein- und Ausgänge
 - Tiefpassfilter 40 - 150 Hz
 - Hochpass/Subsonicfilter 15 - 55 Hz
 - Betriebsmodis: LP-BP / Full / HP
 - Bass-Anhebung 0 - 12 dB
 - Bassfernbedienung
 - Beleuchtetes Logo-Badge
 - Abmessungen: 237 x 55 x 480 mm

A1400 MONOBLOCK

- 1 x 225 Watts RMS into 4 Ohms
 - 1 x 400 Watts RMS into 2 Ohms
 - 1 x 450 Watts Max. into 4 Ohms
 - 1 x 800 Watts Max. into 2 Ohms
 - RCA In- and Outputs
 - Lowpassfilter 40 - 150 Hz
 - Highpass/Subsonicfilter 15 - 55 Hz
 - Operation-Mode: LP-BP / Full / HP
 - Bass Boost 0 - 12 dB
 - Bass Remote Controller
 - Illuminated Logo-Badge
 - Dimensions: 237 x 55 x 310 mm
- 1 x 225 Watt RMS an 4 Ohm
 - 1 x 400 Watt RMS an 2 Ohm
 - 1 x 450 Watt Max. an 4 Ohm
 - 1 x 800 Watt Max. an 4 Ohm
 - Cinch Ein- und Ausgänge
 - Tiefpassfilter 40 - 150 Hz
 - Hochpass/Subsonicfilter 15 - 55 Hz
 - Betriebsmodis: LP-BP / Full / HP
 - Bass-Anhebung 0 - 12 dB
 - Bassfernbedienung
 - Beleuchtetes Logo-Badge
 - Abmessungen: 237 x 55 x 310 mm





A5800 5-CHANNEL

- 4 x 75 + 1 x 150 Watts RMS into 4 Ohms
- 4 x 125 + 1 x 225 Watts RMS into 2 Ohms
- 4 x 150 + 1 x 300 Watts Max. into 4 Ohms
- 4 x 250 + 1 x 550 Watts Max. into 2 Ohm
- RCA Inputs
- 2 x Highpassfilter 10 - 150 Hz (CH 1/2 + 3/4)
- Lowpassfilter 30 - 150 Hz (CH5)
- Bass Boost 0 - 12 dB (CH 5)
- Subsonicfilter 15 - 55 Hz (CH 5)
- Bass Remote Controller
- Illuminated Logo-Badge
- Dimensions: 237 x 55 x 560 mm

- 4 x 75 + 1 x 150 Watt RMS an 4 Ohm
- 4 x 125 + 1 x 225 Watt RMS an 2 Ohm
- 4 x 150 + 1 x 300 Watt Max. an 4 Ohm
- 4 x 250 + 1 x 550 Watt Max. an 2 Ohm
- Cinch Eingänge
- 2 x Hochpassfilter 10 - 150 Hz (CH5)
- Tiefpassfilter 30 - 150 Hz (CH5)
- Bass-Anhebung 0 - 12 dB (CH 5)
- Subsonicfilter 15 - 55 Hz (CH 5)
- Bassfernbedienung
- Beleuchtetes Logo-Badge
- Abmessungen: 237 x 55 x 560 mm

CREATED
FOR THE
STREET



A4150 2-CHANNEL

- 4 x 75 Watts RMS into 4 Ohms
- 4 x 125 Watts RMS into 2 Ohms
- 4 x 150 Watts Max. into 4 Ohms
- 4 x 250 Watts Max. into 2 Ohm
- Highlevel Inputs
- RCA In- and Outputs
- Highpassfilter 60 - 1200 Hz
- Lowpassfilter 30 - 250 Hz
- Bass Boost 0 - 12 db
- Mono bridgeable
- Illuminated Logo-Badge
- Dimensions: 237 x 55 x 340 mm

- 4 x 75 Watt RMS an 4 Ohm
- 4 x 125 Watt RMS an 2 Ohm
- 4 x 150 Watt Max. an 4 Ohm
- 4 x 250 Watt Max. an 2 Ohm
- Hochpegeleingänge
- Cinch Ein- und Ausgänge
- Hochpassfilter 60 - 1200 Hz
- Tiefpassfilter 30 - 250 Hz
- Bass-Anhebung 0 - 12 dB
- Mono brückbar
- Beleuchtetes Logo-Badge
- Abmessungen: 237 x 55 x 340 mm

A2150 2-CHANNEL

- 2 x 75 Watts RMS into 4 Ohms
- 2 x 125 Watts RMS into 2 Ohms
- 2 x 150 Watts Max. into 4 Ohms
- 2 x 250 Watts Max. into 2 Ohms
- Highlevel Inputs
- RCA In- and Outputs
- Highpassfilter 60 - 1200 Hz
- Lowpassfilter 40 - 150 Hz
- Bass Boost 0 - 12 db
- Mono bridgeable
- Illuminated Logo-Badge
- Dimensions: 237 x 55 x 280 mm

- 2 x 75 Watt RMS an 4 Ohm
- 2 x 125 Watt RMS an 2 Ohm
- 2 x 150 Watt Max. an 4 Ohm
- 2 x 250 Watt Max. an 2 Ohm
- Hochpegeleingänge
- Cinch Ein- und Ausgänge
- Hochpassfilter 60 - 1200 Hz
- Tiefpassfilter 40 - 150 Hz
- Bass-Anhebung 0 - 12 dB
- Mono brückbar
- Beleuchtetes Logo-Badge
- Abmessungen: 237 x 55 x 280 mm



STREET MACHINE SUBBOXES



A700BP DUAL BANDPASS

- 2 x 30 cm (12") Subwoofer with 50 mm Voice Coil
- 700 Watts RMS, 1400 Watts Max., Impedance 4 Ohms
- Blue LED-Illumination, Logo-Embroidery
- Dimensions: 780 x 380 x 450/360 mm
- 2 x 30 cm (12") Subwoofer mit 50 mm Schwingspule
- 700 Watt RMS, 1400 Watt Max., Impedanz 4 Ohm
- Blaue LED-Beleuchtung, Logostick
- Abmessungen: 780 x 380 x 450/360 mm

A350BP SINGLE BANDPASS

- 30 cm (12") Subwoofer with 50 mm Voice Coil
- 350 Watts RMS, 700 Watts Max., Impedance 4 Ohms
- Blue LED-Illumination, Logo-Embroidery
- Dimensions: 410 x 380 x 450/360 mm
- 30 cm (12") Subwoofer mit 50 mm Schwingspule
- 350 Watt RMS, 700 Watt Max., Impedanz 4 Ohm
- Blaue LED-Beleuchtung, Logostick
- Abmessungen: 410 x 380 x 450/360 mm

A250BP SINGLE BANDPASS

- 25 cm (10") Subwoofer with 50 mm Voice Coil
- 250 Watts RMS, 500 Watts Max., Impedance 4 Ohms
- Blue LED-Illumination, Logo-Embroidery
- Dimensions: 410 x 340 x 390/310 mm
- 25 cm (10") Subwoofer mit 50 mm Schwingspule
- 250 Watt RMS, 500 Watt Max., Impedanz 4 Ohm
- Blaue LED-Beleuchtung, Logostick
- Abmessungen: 410 x 340 x 390/310 mm



A300BP SINGLE BANDPASS

- 30 cm (12") Subwoofer with 50 mm Voice Coil
- 400 Watts RMS, 800 Watts Max., Impedance 4 Ohms
- Blue LED-Illumination, Logo-Embroidery
- Dimensions: 500 x 380 x 500/300 mm
- 30 cm (12") Subwoofer mit 50 mm Schwingspule
- 400 Watt RMS, 800 Watt Max., Impedanz 4 Ohm
- Blaue LED-Beleuchtung, Logostick
- Abmessungen: 500 x 380 x 500/300 mm



A200BPA ACTIVE BANDPASS

- 20 cm (8") Subwoofer with 50 mm Voice Coil
- 200 Watts Max.
- Gain Controller, variable Lowpass 70 - 200 Hz
- RCA Inputs, High Level Inputs
- Phase Controller 0 - 180°
- Blue LED-Illumination, Logo-Embroidery
- Dimensions: 390 x 290 x 350/280 mm
- 20 cm (8") Subwoofer mit 50 mm Schwingspule
- 200 Watt Max,
- Gain-Regler, variabler Tiefpass 70 - 200 Hz
- Cinch-Eingänge, Hochpegel-Eingänge
- Phasenregler 0 - 180°
- Blaue LED-Beleuchtung, Logostick
- Abmessungen: 390 x 290 x 350/280 mm



A350RX SINGLE BASSREFLEX

- 30 cm (12") Subwoofer with 50 mm Voice Coil
- 350 Watts RMS, 700 Watts Max., Impedance 4 Ohms
- Chrome plated Protection Bars, Logo-Embroidery
- Dimensions: 375 x 385 x 460/350 mm
- 30 cm (12") Subwoofer mit 50 mm Schwingspule
- 350 Watt RMS, 700 Watt Max., Impedanz 4 Ohm
- Verchromte Schutzbügel, Logostick
- Abmessungen: 375 x 385 x 460/350 mm

A250RX SINGLE BASSREFLEX

- 25 cm (10") Subwoofer with 50 mm Voice Coil
- 250 Watts RMS, 500 Watts Max., Impedance 4 Ohms
- Chrome plated Protection Bars, Logo-Embroidery
- Dimensions: 325 x 335 x 400/300 mm
- 25 cm (10") Subwoofer mit 50 mm Schwingspule
- 250 Watt RMS, 500 Watt Max., Impedanz 4 Ohm
- Verchromte Schutzbügel, Logostick
- Abmessungen: 325 x 335 x 400/300 mm



STREET MACHINE

SPEAKERS & ACCESSORIES



A62CX COAXIAL SPEAKERS

- 16.5 cm 2-Way-Coax-System
- 100 Watts RMS, 200 Watts Max. Impedance 4 Ohms
- Frequency Response 50 Hz - 20 KHz
- Mounting Depth 57 mm, Mounting Hole 143 mm

- 16.5 cm 2-Wege-Koax-System
- 100 Watt RMS, 200 Watt Max. Impedanz 4 Ohm
- Frequenzgang 50 Hz - 20 KHz
- Einbautiefe 57 mm, Einbauöffnung 143 mm



A52CX COAXIAL SPEAKERS

- 13 cm 2-Way-Coax-System
- 80 Watts RMS, 160 Watts Max., Impedance 4 Ohms
- Frequency Response 65 Hz - 20 KHz
- Mounting Depth 55 mm, Mounting Hole 116 mm

- 13 cm 2-Wege-Koax-System
- 80 Watt RMS, 160 Watt Max., Impedanz 4 Ohm
- Frequenzgang 65 Hz - 20 KHz
- Einbautiefe 55 mm, Einbauöffnung 116 mm



A42CX COAXIAL SPEAKERS

- 10 cm 2-Way-Coax-System
- 60 Watts RMS, 120 Watts Max., Impedance 4 Ohms
- Frequency Response 80 Hz - 20 KHz
- Mounting Depth 48 mm, Mounting Hole 94 mm

- 10 cm 2-Wege-Koax-System
- 60 Watt RMS, 120 Watt Max., Impedanz 4 Ohm
- Frequenzgang 80 Hz - 20 KHz
- Einbautiefe 48 mm, Einbauöffnung 94 mm



A693TX TRIAXIAL SPEAKERS

- 15 x 23 cm (6 x 9er) 3-Way-Triax-System
- 150 Watts RMS, 300 Watts Max., Impedance 4 Ohms
- Frequency Response 40 Hz - 20 KHz
- Mounting Depth 81 mm, Mounting Hole 151 x 220 mm
- 15 x 23 cm (6 x 9er) 3-Way-Triax-System
- 150 Watts RMS, 300 Watts Max., Impedance 4 Ohms
- Frequency Response 40 Hz - 20 KHz
- Mounting Depth 81 mm, Mounting Hole 151 x 220 mm

A6.2CS COMPONENT SPEAKERS

- 16,5 cm 2-Way-Component-System
- 100 Watts RMS, 200 Watts Max., Impedance 4 Ohms
- Inline-Crossover, 20 mm Neodymium-Tweeter
- Frequency Response 50 Hz - 20 KHz
- Mounting Depth 57 mm, Mounting Hole 143 mm
- 16,5 cm 2-Wege-Komponenten-System
- 100 Watt RMS, 200 Watt Max., Impedanz 4 Ohm
- Inline-Kabel-Frequenzweiche, 20 mm Neodym-Hochtöner
- Frequenzgang 50 Hz - 20 KHz
- Einbautiefe 57 mm, Einbauöffnung 143 mm



AT1200CAP POWER CAP

- Power Capacitor 1,2 Farad Capacity
- 4-digit Voltmeter-Display, solid Acrylic Brackets
- Dimensions: 74/125 x 260 mm
- Pufferelko 1,2 Farad Kapazität
- 4-stellige Spannungs-Anzeige, stabile Acryl-Halterungen
- Abmessungen: 74/125 x 260 mm

AT10KIT AMPLIFIER WIREKIT

- 1 x 10 mm² Power Wire (red), 5 m
- 1 x 10 mm² Ground Wire (grey), 0,8 m
- 1 x RCA Stereo Audio Cable (blue), double shielded, 5 m
- 1 x 0,5 mm² Remote Wire, 5 m
- 1 x AGU Fuseholder with 40 A Fuse
- 1 x 10 mm² Stromkabel (rot), 5 m
- 1 x 10 mm² Massekabel (grau), 0,8 m
- 1 x Cinch Stereo Audio Kabel (blau), doppelt abgeschirmt, 5 m
- 1 x 0,5 mm² Steuerleitung, 5 m
- 1 x AGU Sicherungshalter mit 40 A Sicherung



AT20KIT AMPLIFIER WIREKIT

- 1 x 20 mm² Power Wire (red), 5 m
- 1 x 20 mm² Ground Wire (grey), 0,8 m
- 1 x RCA Stereo Audio Cable (blue), double shielded, 5 m
- 1 x 0,5 mm² Remote Wire, 5 m
- 1 x AGU Fuseholder with 60 A Fuse
- 1 x 20 mm² Stromkabel (rot), 5 m
- 1 x 20 mm² Massekabel (grau), 0,8 m
- 1 x Cinch Stereo Audio Kabel (blau), doppelt abgeschirmt, 5 m
- 1 x 0,5 mm² Steuerleitung, 5 m
- 1 x AGU Sicherungshalter mit 60 A Sicherung



AUTOTEK

EVOLUTION OF POWER



DISTRIBUTION: Audio Design GmbH · Am Breillingsweg 3 · D-76709 Kronau
Tel. +49 (0)7253 - 9465-0 · Fax +49 (0)7253 - 946510 · www.audiodesign.de
© Audio Design GmbH, All Rights Reserved